



ES-BJPX-150L

Thermostatic Incubator Shaker



Cod. ES-BJPX-150L

- Incubator and shaker device that saves space and cost.
- Tempered glass window.
- Mirror surface stainless steel chamber.
- Big LCD screen to display temperature and shaking velocity.
- Working parameters storage function for easy operations.
- Auto-restart after power interruption as originally programmed.
- Auto stop when the door is opened for samples' protection.
- Air spring rods for easy opening and closing.
- Powerful electric motor.
- UV light disinfection function.



TECHNICAL FEATURES

| | |
|-----------------------------------|--------------------------------|
| Shaking speed | 20 ~ 300 rpm |
| Speed precision | ± 1 rpm |
| Oscillation Amplitude | ∅ 26 mm |
| Standard configuration for flasks | 28 x 500 ml |
| Max. volume | 36 x 250 ml |
| Tray size | 920 x 510 mm |
| Timing range | 0 ~ 999h |
| Temperature range | RT +5-60°C (RT:25°C) |
| Temperature precision | ± 0,1°C (constant temperature) |
| Temperature uniformity | ± 1°C |
| Outer size | 120 x 74 x 80 cm |
| Net Weight | 160 Kg |
| Chamber Volume | 970 x 565 x 280mm (155L) |
| Power consumption | 570 W |
| Power supply | AC220V ± 10% 50-60Hz |



Pulse Healthcare Technology
House: 11/1, Shahid Minar Road
Kallyanpur, Dhaka-1216, Bangladesh.
Mobile: +8801708008061
e-mail: info@pht.com.bd
web: www.pht.com.bd



ESSE3 srl, Via Garibaldi 30
14022 Castelnuovo D.B. (AT)
Tel +39 011 99 27 706
Fax +39 011 99 27 506
e-mail esse3@chierinet.it
web: www.esse3-medical.com

