



OPHTHALMIC ACCESSORIES

YZ6F Ophthalmoscope

- Superior optics capability ensure that the ophthalmologist observe eye pathological changes clearly and it suits to small pupil as well
- Import Halogen Lamp, White Spot, Strong and Adjustable Luminance
- Soft startup function ensures the long life of the bulb
- The function of automatism hangup extend the lamp's life span

Specifications

Illumination Form	Big Spot, Small Spot, Slit, Central Net, Redfree
Diopter Compensation	-35D~+20D
Illumination Bulb	3.5V/2.8W Halogen Lamp
Power Supply	AC220V/50Hz



YT2G Advanced Motorized Instrument Table

It adopts lateral column it has a fine appearance and a broad tabletop individualized design makes your job convenient and free

Specifications

Measurement	1200mm(log)x650mm(wide)
Table minimum height/strbke	690mm/190mm
Matimum load	40 kilogram
Input Power supply	Ac220v/ 110v 50/60Hz
The safety standard	IEC601-1、Class Model B

YZ24 Streck Retinoscope




The apparatus is used for measuring reflection and astigmatism observe. It is the best choice for optic shop and ophthalmologist

- 360° rotation filament, up and down movement, accurate or orientation mode rate illumination
- ensure the astigmatism axis quickly and accurately
- The ray can be adjusted to aggregated, parallel and disperse

Specifications

Working Distance	1m
Streak light width	3mm~20mm
Rotation Angle of streak	360°
Illumination Bulb	3V/2W Incandescence Lamp
Power Supply	220V/50Hz



YZ25A Indirect Ophthalmoscope



Used for observing and inspecting eye ground tissue.

- VOLK aspheric lens
- ORSAM'S bulb for illumination
- Filters:redfree,cobalt blue and compensation lens.
- Teaching Tube

Specifications

Angle of Visual Field	45° ± 5°
Range of Pupil Distance	52mm-74mm
Input Voltage	220V/50Hz
Working Voltage	6V/10W Halogen Lamp
Weight (excluding the head bracket)	230 g
Adjustment Range of Head Bracket	530mm-630mm

YZ11D Rechargeable Ophthalmoscope

Specifications

Illumination Source	3.5V/2.8W Halogen Bulb
Power Supply	AC 220V/50Hz or C Size Alkaline Battery
Input Power	8VA
Diopter Compensation:	0, ±1, ±2, ±3, ±4, ±5, ±6, ±8, ±10, +12, -16, ±20, -25, -35 (D)
Illumination Form	Big Spot, Small Spot, Slit, Central Network, Redfree



YZ2A Motorized Instrument Table

It is manufactured under IE601 1. The style capability and quality of the portable has reached advanced International level. The table got the certification of CE and DNV ISO9001. It is the prior choice for the hospital and optical industry.

